

BGR120S

Compact Boarding Gate Reader

An innovative boarding gate solution for the new era of 2D BCBP travel documents.

Description

Access' BGR120S is the world's first boarding gate reader designed to solely accept bar coded documents for airports that have already converted to non-ATB2 encoded documents. Having none of the mechanical complexity required to read ATB2 magnetically encoded coupons, the BGR120S is an extremely compact and easy-to-use solution for boarding gate reader applications.

The BGR120S reads 2D BCBPs and home-printed passes face up, making it easy to align the bar code for instant reading. It is equally suitable for reading bar codes from the screens of cell phones and PDAs.

The near-zero latency imager will read a bar code as soon as it is held in the bright target zone. The device works with IATA recommended PDF417, 2D and linear symbols and its fast omni-directional imager can even read 2D barcode images from a PDA or cell phone display.

The BGR120S has a 2 x 16 character display with bright LED indicators and a user-programmable sounder to provide clear feedback to the operator.

A wide range of emulations is available for connection to Common Use Terminal Equipment (CUTE®) or dedicated systems and, to ensure that the units are future-proof, new firmware can be remotely downloaded into them. Housed in an attractive ABS enclosure, the BGR120S is rugged, compact and lightweight.



The BGR120S reading a bar code from the screen of a PDA



The BGR120S reading a 2D BCBP

Features

- Fast, omnidirectional 1D/2D imager
- Bright VFD 2 x 16 character display
- Reads on presentation of a document
- Reads IATA recommended PDF417, 2D and linear symbologies
- Large document throat allows A4 documents to be read
- Reads 2D barcode images on PDA and cell phone displays
- Wide range of emulations available
- Single RS232 cable connection to host
- FLASH upgradeable software
- Green and red indicator beacons and audio beeper
- Options port to add receipt printer functionality

Options

- Addition of a receipt printer, part number RP9000
- Quick release bracket

Access IS
18 Suttons Business Park
Reading, Berkshire
RG6 1AZ, United Kingdom
Tel: +44 (0) 118 966 3333
Fax: +44 (0) 118 926 7281

Access (North America) inc
PO Box 2569, Peachtree City
Georgia 30269-2569
USA
Tel: +1-770-631-8425
Fax: +1-678-364-8856


Access IS
Interfacing Solutions

For further information email: sales@access-is.com or visit our website: www.access-is.com

All trademarks acknowledged. Specifications subject to change without prior notice. This literature is for outline information only.

Accessories

Quick release bracket



The BGR120S quick release bracket provides a simple means to secure the BGR120S boarding gate reader to a counter-top or podium.

The addition of the bracket prevents the hardware being accidentally knocked to the ground and damaged, potentially at a critical time in boarding. In addition, it is a deterrent against agents easily relocating hardware or theft.

RP9000 receipt printer



The RP9000, a simple, reliable and robust printer for rapid printing of receipts. It can be used to facilitate seat assignment for passengers boarding with 2D bar coded boarding passes on home-printed documents, mobile phones or

PDAs, allowing seat changes to be made at the gate. Additionally, the RP9000 is being used by some airlines to issue boarding pass receipts for all passengers with mobile boarding passes, allowing their mobile phones to be switched off prior to boarding.

BGR120S Boarding Gate Reader

Specifications

Bar code reader

Compliance: AEA2008

1D symbologies: Code 128, Code 2 of 5, Interleaved 2 of 5, IATA 2 of 5, Code 39

2D symbologies: IATA resolution 792, PDF417, Aztec, Datamatrix and QR codes. Will also read from PDA and cell phone displays

Performance: Less than 1 second read capability

Construction: Compact and durable ABS enclosure with no moving parts

Passenger/agent displays

Display: Bright VFD 2 x 16 characters

Visible/audible: Green (good read) and red (bad read) indicator beacons and audio beeper. Programmable capability

Interface

Host interface: RS-232C Baud rates 9600 and 19200; USB

Other: RJ11 port for optional RP9000 receipt printer, keypad or auto boarding gate applications - order model BGR120SR.

The receipt printer can print seat, flight and passenger data from M1 format bar code documents

Physical characteristics

Dimensions: 116W x 114H x 187D mm

Weight: 950 g

Power supply

Input voltage: 9-15 VDC; AC universal power adapter supplied

Protocols supported

ARINC Muse & iMuse[®]

RESA CREWS[®]

SABRE EGR[®]

SITA CUTE[®] NT and APC

Ultra CUSE[®]

Environmental

Temperature: Operating 0 °C to +50 °C; storage 0 °C to +60 °C

Humidity: 0 to 95%, non-condensing

Approvals: FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1

[®] All trademarks acknowledged

Ver: 1.4 September 2009

Access IS
18 Suttons Business Park
Reading, Berkshire
RG6 1AZ, United Kingdom
Tel: +44 (0) 118 966 3333
Fax: +44 (0) 118 926 7281

Access (North America) inc
PO Box 2569, Peachtree City
Georgia 30269-2569
USA
Tel: +1-770-631-8425
Fax: +1-678-364-8856

Access 
Interfacing Solutions

For further information email: sales@access-is.com or visit our website: www.access-is.com

All trademarks acknowledged. Specifications subject to change without prior notice. This literature is for outline information only.